



Decorative Paints and Coatings

Arista

DESCRIPTION

ARISTA is an interior decorative wall paint consist of the mixture of very special acrylic resins. Thanks to its pearlescent pigments, it is glossy, looks elegant and has a variable reflection from different angles due to the light.

APPLICATION AREA

It is used on wall, plaster coating, concrete and wood surfaces after surface preparation with the appropriate primer.

SURFACE PREPARATION

- After cleaning all kinds of dirt, oil, blistered paint and dust from the application surfaces, surface defects should be corrected with SANDECO ACRYLIC PUTTY INTERIOR and primed with SAN DECO DECOPRIMER.
- Painted surfaces should be primed with SAN DECO DECOPRIMER, one layer on light colored surfaces and two layers on dark colored surfaces.

APPLICATION INSTRUCTIONS

- Arista should be mixed homogeneously before the application.
- ARISTA in the selected color is applied with a flat brush or roller on to the surface in a homogeneous way and the pattern is created with the special effects buffer according to the desired effect. Applications on larger areas must be done by two applicator. It is recommended that one applicator applies the product by a roller while the other applicator gives an effect with a buffer before drying starts.
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

DRYING TIME

Allow 2-3 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on surface smoothness, porosity and application methods, for a single coat application;

- 1 lt covers 6 - 7,5 m² of surface
- 1 kg covers 5 - 7 m² of surface
- The paint consumption for 1 m² area is 140-180 ml and 150-200 gr.

STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight at a temperature between +5°C and +35°C.

DEKA BOYA SANAYİ ve TİC. A.Ş.



Decorative Paints and Coatings

Arista

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.


P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)

May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product



Product Technical Data Sheet No. DP.001.ENG - Rev01 November 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88