

PRODUCT DESCRIPTION

MOIRE provides a natural suede appearance on the applied surface thanks to its special components. It creates unique spaces with its matte appearance.

2. APPLICATION AREA

After appropriate surface preparation, it can be used on walls, plaster, raw concrete, wood surfaces, and old painted surfaces in the interiors of spaces, along with Decoprimer.

3. PRODUCT FEATURES

Thanks to its special components, MOIRE creates a natural suede texture and a matte look on the applied surface.

Easy to apply.

The desired effect and texture can be created easily.

At the end of the application, the product creates a suede effect look that will perfectly match your interiors.

It is water-based and has no harm human health or the environment.

4.SURFACE PREPARATION

After cleaning the surfaces to be painted from any dirt, oil, peeling paints, and dust, surface imperfections should be corrected using SAN DECO ACRYLIC PUTTY INTERIOR, followed by priming with SAN DECO DECOPRIMER.

5.APPLICATION INSTRUCTIONS

5.1. Environment and Surface Conditions.

During and for 24 hours after the application, it should be ensured that the ambient temperature remains between +5°C minimum and +35°C maximum.

During the application, it should be ensured that the ambient humidity is below 75%.

Make sure the humidity value of the application surface is lower than 10%.

5.2.Application:

MOIRE is applied in two coats using a brush.

It should be mixed homogeneously without diluting. The same procedure should be followed for both coats during application.

Wait a minimum of 3-4 hours between coats.

In the first coat, MOIRE is applied freely using a brush to achieve the desired appearance.

Repeat the same application technique in the second coat.

You can create your own application methods that suit your style.

In cases where more than one batch is used in the same project, it is recommended that the batches be mixed in equal proportions to prevent batch-based differences.

6.DRYING TIME

At 23°C the touch-drying time is 1-2 hours, and the complete drying time is 24 hours.

7.THEORETICAL CONSUMPTION

For single-layer applications depending on surface smoothness, absorbency, and application techniques;

- 1 lt covers an area of 8 – 12 m².
- 1 kg covers an area of 7 – 10 m².
- Paint consumption per 1 m² is 80 - 130 ml and 100 - 150 gr.

8.STORAGE AND SHELF LIFE

The product can be stored in the original sealed package between +5°C - +35°C temperature for 2 years. Make sure that the product is protected from direct sunlight.

9. HAZARD STATEMENTS

Limit value EU (Directive 2004/42/EC)

Category A/l: Decorative effect coatings (water-based): 200 g/l (2010)

MOIRE content maximum: 20 g/l VOC

H317 May cause an allergic skin reaction.

Precautionary Statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see...on this label).

P272 Contaminated work clothing should not be allowed out of the workplace.

Note: For more information, please check the Safety Data Sheet (SDS) of the product.